

# COTTO WP



## WATER-BASED AND OIL-REPELLENT IMPREGNATING AGENT

- High waterproofing power without altering the appearance of floor
- Also suitable for indoor use
- Ideal for terracotta and natural stones

Specific formulation for the water-oil repellent treatment of terracotta, natural stone and bare concrete. Provides excellent waterproofing without altering the appearance by avoiding the increase of efflorescence.

### HOW TO USE

After carefully removing wax using a wax stripper from the SUTTER PROFESSIONAL range, and after descaling using a special acid (for terracotta floors), apply one or two coats of COTTO WP using the special wax applicator. Leave to dry approximately 30-60 min. between one coat and the next. To get a glossy finish, afterwards apply the product METEOR EXTRA SOLV or a metal wax.



### DILUTION

Ready to use.

### TECHNICAL DATA

**ASPECT:** Clear liquid  
**COLOR:** Colorless/yellow  
**PERFUME:** Lightly technical  
**COV:** 0,00%

PH	Active substance [%]	Density (g/ml)	Pressure (bar)	Viscosity (cP)	Total dry residue [%]
5,1 ± 0,5		1			1,3 ± 0,1

## COTTO WP

### NOTES

Keep away from freezing. Natural protective effect, not film. In case of outdoor finishes, do not apply the product if rain or high humidity are expected. Some floors may be difficult to penetrate and/or anchor the treatment. Check adherence in a small area of the floor before applying the product. Sutter Professional cannot be considered liable for any damages due to improper product use.

**Only for professional use. Safety data sheet available on request.**

### PACKAGING

Code	Size	Quantity	Pallet
4302	Kg 5	4	9x4=36