

METEOR MATT



HIGH RESISTANCE, LOW MAINTENANCE ANTI-SLIP SATIN EFFECT ACRYLIC EMULSION

- Anti-slip effect tested by UL laboratories
- Matt effect
- Reduces frequency of maintenance and costs



Emulsion formulated with an exclusive mixture of polymers and waxes for a special satin effect. Registered with Underwriters Laboratories Inc. as anti-slip, high resistance wax.

HOW TO USE

After carefully removing wax using a wax stripper from the SUTTER PROFESSIONAL range, apply two coats of wax using the special wax applicator. Leave to dry approximately 30 - 60 min. between one coat and the next. Also suitable for UHS spray cleaning or spray buffing maintenance. Recommended maintenance: AZZURRO UL for wet maintenance; RAPID UHS UL for spray method.



DILUTION

Ready to use

TECHNICAL DATA

ASPECT: Opaque liquid

COLOR: Creamy white

PERFUME: Floral

COV: 0,10%

PH	Active substance [%]	Density (g/ml)	Pressure (bar)	Viscosity (cP)	Total dry residue [%]
8,5 ± 0,5		1.023			15 ± 1

METEOR MATT

⚠ WARNINGS

Harmful to aquatic life with long lasting effects. Avoid release to the environment. Dispose of contents/container in accordance with applicable regulations. Contains ZINC AMMONIA CARBONATE COMPLEX, METHYLCHLOROISOTHIAZOLINONE, METHYLISOTHIAZOLINONE. May produce an allergic reaction

📝 NOTES

Protective wax for floors. Do not apply METEOR MATT at temperatures below 10° C. Keep away from freezing. Some floors may be difficult to penetrate and/or anchor the treatment. Check adherence in a small area of the floor before applying the product. Sutter Professional cannot be considered liable for any damages due to improper product use.

Only for professional use. Safety data sheet available on request.

📦 PACKAGING

Code	Size	Quantity	Pallet
4020	Kg 5	4	9x4=36