

UNISPLEND



HIGH CONCENTRATION, ANTI-SLIP ACRYLIC EMULSION

- Anti-slip effect tested by UL laboratories
- One-coat application
- Suitable for spray cleaning and spray buffing systems



Emulsion formulated with a high concentration of acrylic polymers, waxes and resins. Suitable for one-coat applications. Registered with Underwriters Laboratories Inc. as anti-slip, high resistance wax.

HOW TO USE

After carefully removing wax using a wax stripper from the SUTTER PROFESSIONAL range, apply just one coat of wax using the special wax applicator. Also suitable for UHS spray cleaning or spray buffing maintenance. Recommended maintenance: AZZURRO UL for wet maintenance; RAPID UHS UL for spray method.



DILUTION

Ready to use.

TECHNICAL DATA

ASPECT: Opaque liquid

COLOR: Creamy white

PERFUME: Floral

COV: 0,10%

PH	Active substance [%]	Density (g/ml)	Pressure (bar)	Viscosity (cP)	Total dry residue [%]
8,0 ± 0,5		1.047			28 ± 1

UNISPLEND

! WARNINGS

May cause an allergic skin reaction. Harmful to aquatic life with long lasting effects. Avoid breathing vapours. Wear protective gloves and eye/face protection. If skin irritation or rash occurs: Get medical advice/attention. Take off contaminated clothing and wash it before reuse. Contains METHYLCHLOROISOTHIAZOLINONE, METHYLISOTHIAZOLINONE. May produce an allergic reaction. Contains ZINC AMMONIA CARBONATE COMPLEX.



WARNING

📄 NOTES

Do not apply UNISPLEND at temperatures below 10° C. Keep away from freezing. Some floors may be difficult to penetrate and/or anchor the treatment. Check adherence in a small area of the floor before applying the product. Sutter Professional cannot be considered liable for any damages due to improper product use.

Only for professional use. Safety data sheet available on request.

📦 PACKAGING

Code	Size	Quantity	Pallet
4015	Kg 5	4	9x4=36